

AU version LED downlight & T8 LED tube



Model	Description
H-D-CTH10F	10W $\phi 85 \times 80$ mm Cut-out: 65-70mm 700lm
H-D-CTH15F	15W $\phi 110 \times 110$ mm Cut-out: 75-80mm 800lm
H-D-CTH18F	18W $\phi 110 \times 110$ mm Cut-out: 90-95mm 950lm



Model	Description
H-T-ST809	600mm 9W 900-1000lm
H-T-ST812	900mm 12W 1200-1400lm
H-T-ST818	1200mm 18W 1800-2000lm
H-T-ST824	1500mm 24W 2200-2800lm
H-T-ST826	1500mm 26W 2400-3000lm



Traditional design LED downlight & LED bulb



High LED luminous intensity, adopting transparent optical principle and anti-dazzle design, avoid direct glare into the eyes effectively and ensure the light transmittance.

Model	Description
H-D-C60FX18	20W cut-out $\phi 170$ 1600lm
H-D-C80FX30	30W cut-out $\phi 202$ 2300lm



E27, E26, B22 base for choice. Available in warm white 3000K, neutral white 4000K, cool white 6000K. EMC, LVD and SAA fully certified.

Model	Description
H-B-SA6006	6W $\phi 60 \times 125$ mm 480lm
H-B-SA6008	8W $\phi 60 \times 125$ mm 640lm
H-B-SA6010	10W $\phi 60 \times 125$ mm 800lm
H-B-SA6012	12W $\phi 60 \times 125$ mm 960lm



Optoelectronic Components

Commercial & office lighting: LED Downlight, Tubes, Panels and Spotlight;
Smart residential lighting: LED Bulbs, Downlight.

Booth NO.: 1B-E27
April 6-9th 2015, HK

HOLY LIGHTING TECHNOLOGY CO., LTD.

<http://www.ledholy.com> Email: info@ledholy.com


Tel: 86-755-28231116 Fax: 86-755-22640617

Add: 1169-2, shenhui Rd, Henggang street, Longgang district, Shenzhen, China

On/off Change Smart LED Bulb



- On/off switch control
- Memory smart module
- 3 color temperature modes



One LED Bulb

Three Color Temperature Experience

Features:


1. Adjust color temperature easily by switching twice continuously(WW–NW–CW), and repeat.
2. The bulb would remember current color temperature after adjustment. Only need to switch normally next time.
3. Color temperature: 3000K–6000K.



On/off Change Smart LED downlight



- On/off switch control
- Memory smart module
- 3 color temperature modes



One LED Downlight

Three Color Temperature Experience

Features:


1. Adjust color temperature easily by switching twice continuously(WW–NW–CW), and repeat.
2. The bulb would remember current color temperature after adjustment. Only need to switch normally next time.
3. Color temperature: 3000K–6000K.



WIFI Smart LED bulb & LED downlight



- 2.4G RF & WIFI control
- iOS APP/Android APP
- 3 color temperature modes



WIFI Smart LED bulb

Model	Description
H-B-SA6006CTW6W	φ60×110mm 480-520lm

WIFI Smart LED downlight

Model	Description
H-D-S30KS06CTW	6W φ100×50mm Cut-out: 85-90mm 480-520lm

